



MINI 2000



Specifications

Accessories

Item	Product Code	Description
PC Interface	MN-INT	PC interface connecting to your computer's serial port
ESCORT Console	JA-SWP-WIN	Free Software for programming and data download available on the Internet www.EscortDLS.com
ChartReader	MN-CR	Portable printer for on site printing of data
ChartReader with memory	MN-CR-MEM	Portable printer with memory for storing up to 1 million readings by different MINI 2000 loggers
ChartReader Interface	JA-CHR-INT-E	PC Interface for ChartReader programming and data download
ChartReader Connector	MN-CR-INT	Cable connecting MINI 2000 logger to ChartReader
Start magnet	JA-KEY	Start magnet in form of key ring

Specifications

Operating Temperature	-40/70°C
Storage temperature	-40/70°C
Accuracy	±0.3°C
Resolution	0.5°C
Memory	2,000 samples
Weight	42 grams
Temperature response	T90 of 20 minutes in moving air for Internal, 5 minutes for external
Time and date	Real time clock, accuracy better than 40 seconds per month at ambient
Traceability	Temperature Calibration can be provided to ISO 9002
Sampling frequency	1 to 255 minutes
Power source	3V Lithium Battery, not replaceable
Typical battery life	1 year (dependent on frequency of PC communication)
Case material	ABS
IP Rating	IP51
Size (HxWxD)	80mm x 52mm x 16mm (excluding lug)
Data recovery	Via plug-in interface and IBM compatible PC
Software	ESCORT Console for Windows® 98, NT or later
Recorder start up	Programmed time and date or magnet swipe
Warranty	12 months (excluding batteries)